

PRODUCT DATA SHEET

SERVO KOOL HWC 50



DESCRIPTION

Servo Kool HWC 50 is a triple action long life radiator coolant prepared from selected ingredients to meet the highest Japanese standard and is free from Amines, Borates, Nitrates and Silicates and Phosphates.

APPLICATION

Servo Kool HWC 50 is recommended by TAFE for use as a radiator coolant in the tractors. Servo Kool HWC is compatible with hard water having hardness even upto 700 ppm.

PERFORMANCE BENEFITS

- Does not boil and vaporise in the hottest summer or freeze in severe winter.
- Prevents corrosion of radiator components and other parts.
- Increases cooling efficiency.
- Reduces maintenance costs and increases radiator life.
- Free from Amines, Borates, Nitrates and Silicates and Phosphates.
- Compatible with hard water.

MANUFACTURERS APPROVAL

Recommended for use as engine coolant by M/s. TAFE for use in their tractors.

CHARACTERISTICS

| | |
|--|-------------------|
| Appearance | Blue clear liquid |
| Specific Gravity @ 20°C, Min. | 1.0804 |
| Boiling Point, °C, Min | 109 |
| Freezing Point, °C 30% Volume Solution 50% Volume Solution | |
| pH of 30 v/v % Soln in distilled water | 7.5 – 9.0 |

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20