

# PRODUCT DATA SHEET

## SERVO KOOL HY



### DESCRIPTION

Servo Kool HY is a triple action long life radiator coolant prepared from selected corrosion inhibitors to meet the requirements of M/s. Hyundai Motors with specific reference to cast aluminium corrosion.

### APPLICATION

Servo Kool is mixed in the ratio of 30 parts of the coolant to 70 parts of distilled water.

### PERFORMANCE BENEFITS

- Does not boil and vaporise in the hottest summer or freeze in severe winter.
- Prevents corrosion of radiator made of cast Aluminium and other parts.
- Increases cooling efficiency.
- Reduces maintenance costs and increases radiator life.

### PERFORMANCE STANDARDS

- MS 591-08 LLC2 of M/s. Hyundai Motors.

### CHARACTERISTICS

|  |                                |
|--|--------------------------------|
| Appearance                                     | Green with yellow fluorescence |
| Boiling Point, °C, Min                         | 150                            |
| Freezing Point                                 |                                |
| 30% Volume Solution, °C                        | (-) 14.5 Max                   |
| 50% Volume Solution, °C                        | (-) 34 Max                     |
| pH of 30 v/v % solution in distilled water, ml | 7.5 – 8.5                      |
| Density gms/ml at 29.5 Deg C                   | 1.10 – 1.14                    |

### HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

**E-Mail:** servotechserv@indianoil.in **OR** servots@indianoil.in

May-20