

### DESCRIPTION

Servo Maijo OBM Special is low smoke semi-synthetic two stroke engine oil developed to meet the critical requirements of high performance water cooled two stroke engines where NMMA TC-W3 performance lubricants are specified. It is blended from selected base stocks and superior additives systems to minimise spark plug fouling and preignition, prevent rusting, minimise deposit formation and provide protection against seizure, scuffing and wear. It contains a diluent for easy mixing with gasoline.

### APPLICATION

Servo Maijo OBM Special is recommended for lubrication of two stroke outboard engines. Suitable for use in premix and Regular and Xtra-Premium Petrol for fuel/oil mixture ratios as recommended by the Original engine manufacturer.

### PERFORMANCE BENEFITS

- ☞ Excellent engine cleanliness
- ☞ Minimizes spark plug fouling
- ☞ Reduces Engine Deposits
- ☞ Outstanding Rust Inhibiting qualities.
- ☞ Is easily pumpable by oil injection system
- ☞ Low Ash product. Prevents auto ignition.
- ☞ Keep the fuel lines clean
- ☞ Suitable for Modern High Power Engines.

### PERFORMANCE STANDARDS

Meets

- ☞ Latest NMMA TC-W3 specifications including Lubricity Performance.

### CHARACTERISTICS

Appearance	Clear
Kinematic Viscosity @ 40°C, CST	42-60
Kinematic Viscosity @ 100°C, CST	7.4
Flash Point (PMCC), °C, Min	90
Pour Point, °C, Max	(-) 30

### HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

**E-Mail:** servotechserv@indianoil.in **OR** servots@indianoil.in

May-20