

PRODUCT DATA SHEET

SERVO ROCK 4T PLUS



DESCRIPTION

Servo Rock 4T Plus is high performance engine oil for 4 stroke motorbikes. This oil is a high viscosity index, four stroke superior performance engine oil formulated for the motorbikes of M/s. Global Automobiles Ltd.

APPLICATION

Servo Rock 4T Plus is recommended for use as engine oil in 4 stroke motorbikes of M/s. Global Automobiles Ltd.

PERFORMANCE BENEFITS

- ☛ Maximum power output.
- ☛ Superior performance in terms of oxidation stability.
- ☛ Excellent wear protection at high temperatures and severe operating conditions.
- ☛ Outstanding overall engine cleanliness.
- ☛ Enhanced engine & gear life.
- ☛ Higher fuel efficiency.
- ☛ Extended engine oil life

PERFORMANCE STANDARDS

- ☛ API SJ, JASO MA 2 and meeting API SL specification for Valve train wear with a viscometrix of SAE 10W-30.

MANUFACTURERS APPROVAL

Approved by M/s. Global Automobiles Ltd. for use as Engine Oil in four stroke motorbikes.

CHARACTERISTICS

SAE GRADE	10W-30
Kin. Viscosity @ 100°C, cSt	10 - 12
Viscosity Index, Min.	130
Flash Point, COC, °C, Min	190
Pour Point, °C, Max	(-) 27
TBN, mg KOH/gm	6.8 – 8.2
Sulphated Ash , % wt	0.95 – 1.2

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20