

# PRODUCT DATA SHEET

## SERVO SCOOTOMATIC 10W-40



### DESCRIPTION

Servo Scootomatic 10W-40 is high performance engine oil specially formulated for 4 stroke gearless scooters. This oil is blended from high viscosity index base stocks and contains additives to meet the performance standards for gearless scooters.

### APPLICATION

Servo Scootomatic 10W-40 is recommended for engine & transmission systems of new generation 4 stroke gearless scooters, such as GUSTO of Mahindra 2 wheelers.

### PERFORMANCE BENEFITS

- ☞ Superior pick up at all times
- ☞ Smooth engine performance
- ☞ Unique formulation made for modern gearless scooters.
- ☞ Enhanced engine life.
- ☞ Lower friction
- ☞ Superior thermal protection.
- ☞ Longer drain intervals

### PERFORMANCE STANDARDS

- API SL & JASO MB

### APPROVALS

- Mahindra 2 wheelers for Engine & transmission system of GUSTO scooter.

### CHARACTERISTICS

SAE GRADE	10W-40
Kin. Viscosity @ 100°C, cSt	13.5 – 15.5
Viscosity Index, Min.	135
Flash Point, COC, °C, Min	200
Pour Point, °C, Max	(-) 27
TBN, mg KOH/gm	6.4 – 8.4
Sulphated Ash % wt	0.71 – 0.98

### HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

**E-Mail:** servotechserv@indianoil.in **OR** servots@indianoil.in

May-20