

PRODUCT DATA SHEET

SERVO 2T SUPREME



DESCRIPTION

Servo 2T Supreme is low smoke semi-synthetic two stroke engine oil developed to meet the critical requirements of high performance two stroke engines manufactured by leading auto makers. It is blended from selected base stocks and additives to minimise spark plug fouling and preignition, prevent rusting, minimise deposit formation and provide protection against seizure, scuffing and wear. It contains a diluent for easy mixing with gasoline. Servo 2T Supreme is green dyed product.

PERFORMANCE BENEFITS

- ☞ Low exhaust smoke
- ☞ Maintains engine cleanliness
- ☞ Minimises spark plug fouling
- ☞ Reduces port deposits and ring sticking
- ☞ Prevents seizure and scuffing
- ☞ Is easily pumpable by oil injection system

APPLICATION

Servo 2T Supreme is recommended for lubrication of scooters, autorickshaws, motorcycles and mopeds operating on two stroke engines. The recommended dosage of Servo 2T Supreme is 20 ml of oil per litre of petrol.

PERFORMANCE STANDARDS

- ☞ JASO FC specifications.
- ☞ API TC Specification

Manufacturers Approval

- ☞ Servo 2T Supreme is approved by leading two stroke 2 and 3 wheelers manufacturers having petrol and oil injection lubrication system.

CHARACTERISTICS

Colour	Green
Kinematic Viscosity @ 40°C, cSt	55-60
Kinematic Viscosity @ 100°C, cSt	8.6
Sulphated ash % wt.,	0.078-0.095
Pour Point, Deg C	(-) 12
Flash Point (PMCC), °C, Min	70

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20