

# PRODUCT DATA SHEET

## SERVO FUTURA SYNTH PLUS 5W-30



### DESCRIPTION

Servo Futura Synth Plus 5W-30 is blended with 100% synthetic base stocks blended with synergistic additive system for outstanding detergency, dispersancy characteristics, anti-wear and antioxidant properties, high viscosity index and low temperature flow properties. The additive chemistry and dosage are carefully optimized for control on elements resulting in retention of effectiveness of catalytic converters. This delicately balanced composition provides and exceeds tough industry performance standards thus ensuring reliability, emission control economy and endurance.

### APPLICATION

Servo Futura Synth Plus 5W-30 is recommended for gasoline and diesel engines of Hyundai & other new generation passenger cars and vehicles.

### PERFORMANCE BENEFITS

- Fully synthetic engine oil recommended for high-performance petrol and diesel engines.
- Better low and high temperature performance.
- Meets the strictest emission standards.
- Formulated for extra wear protection for long life of oil and engine.
- Exhibits very high oxidation stability to withstand high temperature and high load engine conditions preventing sludge build up.
- Extended drain intervals upto 20,000 Kms

### SPECIFICATIONS

Servo Futura Synth Plus 5W-30 meets ACEA A5/B5, API SN and OEM Specifications

### CHARACTERISTICS

Kinematic Viscosity, cSt, @ 100°C	9.3 – 12.5
Viscosity Index, Min	160
Flash Point (COC), °C Min.	230
Pour Point, °C, Min	(-) 30
TBN, mg KOH/gm	10.2
HTHS Viscosity, cP, Min	3.29

### HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

**E-Mail:** servotechserv@indianoil.in **OR** servots@indianoil.in

May-20