

SERVO SUPER DS

DESCRIPTION

Servo Super DS is heavy duty engine oils for diesel service. These oils are blended from selected highly refined, high viscosity index base stocks and contain well balanced group of additives, to provide high detergency, dispersancy and anti oxidation characteristics to meet the stated performance standards.

APPLICATION

Servo Super DS is recommended for:

- Naturally aspirated, supercharged and turbocharged diesel engines.
- High powered gasoline engines
- Mixed fleet operation

PERFORMANCE BENEFITS

Servo Super DS oils

- Provide excellent resistance against wear and deposits in automotive supercharged diesel engines
- Have exceptional thermal and oxidation stability to resist decomposition in supercharged engines operating with high ring zone temperature.
- Provide absolute control of corrosive wear that may result from use of high sulphur fuels because of good built-in alkaline reserves.
- Maintain a high order of engine cleanliness

PERFORMANCE STANDARDS

Servo Super DS oils meet the following specifications:

- US MIL-L 2104C
- API CF/CD
- E-DL 3 of IS:13656-2002
- MACK T-7 test for oil thickening tendency.
- Sequence III F

CHARACTERISTICS

SAE GRADE	10W	30	40	50
Kin. Vis. cSt @ 100°C	5Min.	10 – 12	13 – 15	18 – 20
Viscosity Index, Min.	100	95	90	90
Flash point (COC), °C Min.	190	220	220	230
Pour Point, °C Max.	(-)27	(-) 6	(-) 6	(-) 6
TBN mg KOH/gm	9.5–12.5	9.4–12.5	9.4–12.5	9.4–12.5

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: tsservices@indianoil.co.in **OR** tech_services@indianoil.co.in