

## SERVO XEE SM 5W-40

### DESCRIPTION

Servo XEE SM 5W-40 oil is high performance engine oil for new generation petrol vehicles. This oil is fully synthetic and contain selected additives to meet the highest performance standards for petrol vehicles.

### APPLICATION

Servo XEE SM 5W-40 is recommended for new generation passenger cars using petrol. This oil is also recommended for diesel vehicles.

### PERFORMANCE BENEFITS

- ☛ Superior performance in terms of oxidation stability, dispersancy characteristics and energy efficiency.
- ☛ Excellent sludge control and extra wear protection at high temperatures and severe operating conditions.
- ☛ Outstanding overall engine cleanliness and also provide long engine life.
- ☛ Fuel savings and nil oil top up.
- ☛ Catalytic Converter Compatible.

### PERFORMANCE STANDARDS

- ☛ Meets API SM/CF
- ☛ Meets MB 229.1

### CHARACTERISTICS

SAE GRADE	5W-40
Kin. Viscosity @ 100°C, cSt	13 – 14
Viscosity Index, Min.	150
Flash Point, COC, °C, Min	200
Pour Point, °C, Max	(-) 51
TBN, mg KOH/gm	9.0 – 11.0

### HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

**E-Mail:** [tsservices@indianoil.co.in](mailto:tsservices@indianoil.co.in) OR [tech\\_services@indianoil.co.in](mailto:tech_services@indianoil.co.in)