

PRODUCT DATA SHEET

SERVO FUTURA P 10W40



SERVO®

DESCRIPTION

Servo Futura P 10W40 is a long life, high performance engine oil compatible for Petrol & Diesel engines conforming to advance emission norms. This oil is highly refined high viscosity index base stocks and contain additives to meet the highest performance standard for modern Engines.

APPLICATION

Servo Futura P 10W40 is recommended for new generation Petrol & Diesel vehicles conforming to advanced emission norms..

PERFORMANCE BENEFITS

- ☞ Increased component life.
- ☞ Excellent Engine Cleanliness.
- ☞ Excellent control on soot induced oil thickening.
- ☞ Outstanding control on oil consumption.
- ☞ Ensures outstanding protection from wear, high temperature deposits, oil degradation and corrosion.
- ☞ Suitable for diesel vehicles with EGR

PERFORMANCE STANDARDS

- SAE 10W40 : Meets API SM requirement for petrol engine.
- Meets ILSAC GF 4 performance

CHARACTERISTICS

SAE GRADE	10W-40
Kin. Viscosity @ 100°C, cSt	13.5 – 15.5
Viscosity Index, Min	135
Flash Point, COC, °C, Min	190
Pour Point, °C, Min.	(-) 27
TBN, mg KOH/gm	7 – 8.5
Sulphated Ash % wt	0.75 – 0.92

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: tsservices@indianoil.co.in **OR** tech_services@indianoil.co.in

May-20