

PRODUCT DATA SHEET



SERVO[®]

SERVO SYNCHRO 80W-90 (M)

DESCRIPTION

Servo Synchro 80W-90 (M) is extreme pressure automotive gear oil. This oil is blended from selected base stocks and contain special additive system to provide extreme pressure characteristics for wear protection.

APPLICATION

Servo Synchro 80W-90 (M) oil is recommended for synchromesh gear box and transfer case of Multi Utility Vehicles of Mahindra & Mahindra viz. Scorpio, Balero etc.

PERFORMANCE BENEFITS

Servo Synchro

- Provide protection against wear, due to good EP characteristics
- Give long service life even under high temperature operation since it has excellent oxidation stability
- Provide good protection against corrosion.
- Extended oil drain interval.
- Superior gear shift feel characteristics.

PERFORMANCE STANDARDS

Servo Synchro meets:

- API Service GL 4 SAE 80W-90

CHARACTERISTICS

SAE GRADE	80W-90 (M)
Kinematic Viscosity cSt @ 100°C	14.5 –16
Viscosity Index, Min.	90
Flash point (COC), °C Min.	180
Pour Point, °C Max.	(-) 27
Copper Corrosion @ 121°C, 1 hr, Max	1

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: tsservices@indianoil.co.in OR tech_services@indianoil.co.in

May-20