



DESCRIPTION

Servo Syngear Super 75W90 is a new technology synthetic automotive gear oil combined with suitable performance additive to provide high temperature thermal stability and metal compatibility at elevated temperatures.

APPLICATION

Servo Syngear Super 75W90 is recommended for passenger car, bus and highway truck hypoid, spiral bevel and worm gear axles and also manual transmission for which an extreme pressure gear lubricant of this type is required.

PERFORMANCE BENEFITS

- Reduced wear due to high load carrying capacity.
- Extended component life.
- Increased oil life.
- Low maintenance costs.
- Wide temperature application.
- Excellent resistance to oxidation and aging.
- High temperature thermal stability.

PERFORMANCE STANDARDS

Servo Syngear Super 75W90 is meeting SAE 75W90 API GL 5 specification.

CHARACTERISTICS :

ISO VG GRADE	75W90
K. Vis. @ 40°C, cSt	90
K. Vis. @ 100°C, cSt (T)	15
Viscosity Index, Min	178
Flash Point, COC, °C, Min	190
Pour Point, °C, Max	(-) 42
TAN mg KOH/gm (T)	0.98
FZG Load Stage, Pass	12

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: tsservices@indianoil.co.in **OR** tech_services@indianoil.co.in

May-20