

PRODUCT DATA SHEET

SERVO CHHAKADA ENGINE OIL



DESCRIPTION

Servo Chhakada engine oil is high performance Diesel engine oils. This oil is blended from high viscosity index base stocks and contain additives to meet the stated performance standards. This oil can be used in 3 Wheelers for Transporting Goods and Public in the Terrain and non-Terrain regions.

APPLICATION

Servo chhakada engine oil is recommended for new generation 4 stroke 3 wheelers operated on diesel fuel. This oil is also suitable for existing load/passenger carrying four stroke three wheelers i.e. scooters and motorcycles.

PERFORMANCE BENEFITS

- ☛ Superior performance in terms of oxidation stability, dispersancy characteristics and energy efficiency.
- ☛ Excellent sludge control and extra wear protection at high temperatures and severe operating conditions.
- ☛ Outstanding overall engine cleanliness and also provide long engine life.
- ☛ Fuel savings and low oil top up.
- ☛ Catalytic Converter Compatible.

PERFORMANCE STANDARDS

- ☛ API SC in gasoline and CC in diesel service.
- ☛ US MIL-L-2104 B
- ☛ E-PL 1/ E-DL 1 of IS:13656 - 2002

CHARACTERISTICS

SAE GRADE	20W-40
Kin. Vis. @ 100°C, cSt	13.5 – 15.5
Flash Point, COC, °C, Min	200
Pour Point, °C, Max	(-) 21
TBN mg KOH/gm	4.5 – 6.0

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: tservices@indianoil.co.in **OR** tech_services@indianoil.co.in