

PRODUCT DATA SHEET

SERVO PRIDE MAX 15W-40



DESCRIPTION

Servo Pride MAX 15W-40 is top of the shelf low Sulphated Ash, Phosphorous and Sulphur (SAPs) premium quality diesel engine oil. The oil is designed for the most severe performance requirements of latest diesel engines vehicles operating with Ultra low sulphur diesel (sulphur content 15 ppm Max). It assures outstanding protection against high temperature engine deposits, oil degradation, oil thickening and corrosion resistance, soot related wear control. It also covers the requirement of API CI 4 and CI 4 Plus engine oils.

PERFORMANCE BENEFITS

- # Reduced engine scuffing and bore polishing.
- # High engine cleanliness.
- # Maximum protection from wear and deposits.
- # Improved control of oil consumption.
- # Easier cold starting.
- # Excellent all weather performance due to improved cold weather properties.

APPLICATION

Servo Pride MAX is recommended for latest generation commercial diesel vehicles of both American and European design. It is tailor made to the lubrication requirements of engines complying to EURO IV emission requirement. This oil is especially effective at sustaining emission control system durability where particulate filters and other advanced after treatment systems are used. Optimum protection is provided for control of catalyst poisoning, particulate filter blocking, engine wear, piston deposits, low and high temperature stability, soot handling properties, oxidative thickening, foaming, and viscosity loss due to shear.

PERFORMANCE STANDARDS

- * API CJ-4
- * ACEA E-9

CHARACTERISTICS

SAE GRADE	15W-40
Kinematic Viscosity, cSt @ 100°C	14.5 - 15.5
Viscosity Index, Min.	135
TBN, mg KOH/g	12.2 - 15.0
Flash Point, (COC)°C, Min.	200
Pour Point °C, Max.	(-) 24
Sulphated Ash, % wt.	0.87 - 1.01
CCS @ -25 Deg C	7000 Max

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: tservices@indianoil.co.in **OR** tech_services@indianoil.co.in

May-20