

PRODUCT DATA SHEET

SERVO PRIDE XL 5W-40



DESCRIPTION

Servo Pride XL 5W-40 oil is a fully synthetic superior performance engine oil recommended for new generation diesel vehicles operated in sub zero condition under heavy load. Formulated with very high viscosity index synthetic base oil to provide better protective film at high temperature.

APPLICATION

Servo Pride XL oil is recommended for new generation diesel engines to provide outstanding high temperature detergency and smooth operation at sub zero temperature under heavily loaded conditions.

PERFORMANCE BENEFITS

Provides rapid cold engine starters.

- ☞ Very low oil consumption due to low volatility.
- ☞ Superior wear protection.
- ☞ Superior resistance to thermal degradation and oxidation.
- ☞ Optimum engine life.
- ☞ Safe for highly loaded and thermally stressed engines.
- ☞ Extended drain interval.
- ☞ Outstanding low temperature pumping

PERFORMANCE STANDARDS

- ☞ API CH 4 for diesel and API SL for petrol engine.
- ☞ MB 228.3
- ☞ CES 20076
- ☞ VDS 3
- ☞ Global DHD 1

CHARACTERISTICS

SAE GRADE	5W-40
Kin. Viscosity @ 100°C, cSt	13.5 – 15.0
Viscosity Index, Min	150
Flash Point, COC, °C, Min	226
Pour Point, °C, Min.	(-) 45
TBN, mg KOH/gm	9 – 11

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: tsservices@indianoil.co.in **OR** tech_services@indianoil.co.in

May-20