

PRODUCT DATA SHEET

SERVO PRIDE XL 15W-40-M



DESCRIPTION

Servo Pride XL 15W-40-M is premium multipurpose diesel engine oil. The oil is designed for the most severe performance requirements of diesel operated MUL vehicles. It assures outstanding protection against high temperature engine deposits, oil degradation, oil thickening and corrosion resistance. The oil is having excellent shear stability to maintain viscosity under severe, high temperature operations. It exhibits outstanding control on soot induced thickening and soot induced wear.

PERFORMANCE BENEFITS

- # Reduced engine scuffing and bore polishing.
- # High engine cleanliness.
- # Maximum protection from wear and deposits.
- # Improved control of oil consumption.
- # Easier cold starting.
- # Excellent all weather performance due to improved cold weather properties.
- # Has the potential of long drain interval.

APPLICATION

Servo Pride XL 15W-40-M is recommended for Maruti diesel vehicles. It is tailored to the lubrication requirements of engines complying to EURO III.

PERFORMANCE STANDARDS

- * API CH-4
- * MB 228.3
- * VOLVO VDS-3
- * Cummins CES 20076
- * ACEA E 3

MANUFACTURERS APPROVAL

Approved by M/s. Maruti Udyog Ltd., as engine oil for all maruti make diesel vehicles.

CHARACTERISTICS

SAE GRADE	15W-40
Kinematic Viscosity, cSt @ 100°C	13.5 – 15.5
Viscosity Index, Min.	135
TBN, mg KOH/g	10.0 – 11.5
Flash Point, (COC)°C, Min.	200
Pour Point °C, Max.	(-) 24

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: tsservices@indianoil.co.in **OR** tech_services@indianoil.co.in

May-20