

PRODUCT DATA SHEET

SERVO SUPER PLUS 20W-40



DESCRIPTION

Servo Super Plus 20W 40 is a heavy duty diesel engine oil. This oil is blended from selected highly refined, high viscosity index base stocks and contain well balanced group of additives, to provide high detergency, dispersancy and anti oxidation characteristics to meet the stated performance standards.

APPLICATION

Servo Super Plus 20W 40 is recommended for naturally aspirated, highly supercharged and turbocharged diesel engines operating under severe duty conditions in all seasons .

PERFORMANCE BENEFITS

Servo Super Plus oil

- Provide excellent resistance against wear and deposits in automotive supercharged diesel engines
- Have exceptional thermal and oxidation stability to resist decomposition in supercharged engines operating with high ring zone temperature.
- Provide absolute control of corrosive wear that may result from use of high sulphur fuels because of good built-in alkaline reserves.
- Maintain a high order of engine cleanliness

PERFORMANCE STANDARDS

Servo Super Plus oil meets the following specifications:

- US MIL-L 2104C
- API CF/CD
- E-DL 3 of IS:13656-2002
- Caterpillar Series 3
- MACK T-7 test for oil thickening tendency.
- Sequence III F

CHARACTERISTICS

SAE GRADE	20W- 40
Kin. Vis. cSt @ 100°C	13.5 – 15.5
Viscosity Index, Min.	110
Flash point (COC), °C Min.	200
Pour Point, °C Max.	(-) 21
TBN mg KOH/gm	9.5–12.5

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: tsservices@indianoil.co.in **OR** tech_services@indianoil.co.in

May-20