

# PRODUCT DATA SHEET

## SERVO MIL C 40



# SERVO<sup>®</sup>

### DESCRIPTION

Servo MIL C 40 oil is heavy duty engine oil for diesel service. This oil is red in colour and blended from selected highly refined, high viscosity index base stocks and contain well balanced group of additives, to provide high detergency, dispersancy and anti oxidation characteristics to meet the stated performance standards.

### APPLICATION

Servo MIL C 40 oil is recommended for:

- Naturally aspirated, supercharged and turbocharged diesel engines.
- Mixed fleet operation

### PERFORMANCE BENEFITS

Servo MIL C 40 oil is

- Provide excellent resistance against wear and deposits in automotive supercharged diesel engines
- Have exceptional thermal and oxidation stability to resist decomposition in supercharged engines operating with high ring zone temperature.
- Provide absolute control of corrosive wear that may result from use of high sulphur fuels because of good built-in alkaline reserves.
- Maintain a high order of engine cleanliness

### PERFORMANCE STANDARDS

Servo MIL C 40 oil meet the following specifications:

- API CF/CD
- E-DL 2 of IS:13656-2002

### CHARACTERISTICS

SAE GRADE	40
Kin. Vis. cSt @ 100°C	13 – 15
Viscosity Index, Min.	90
Flash point (COC), °C Min.	220
Pour Point, °C Max.	(-) 6
TBN mg KOH/gm	7.7 – 11.5

### HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

**E-Mail:** [tsservices@indianoil.co.in](mailto:tsservices@indianoil.co.in) **OR** [tech\\_services@indianoil.co.in](mailto:tech_services@indianoil.co.in)

May-20