

DESCRIPTION

Servo Taxi oil 20W-50 is blended from highly refined base stocks and balanced additive package containing shear stable VI improver, metallic detergent dispersant and anti-oxidant. This oil is formulated to meet lubrication requirements of both diesel and gasoline engines.

APPLICATION

Servo Taxi Oil is recommended for models of petrol and diesel engine having 20W-50 grade. Vehicles encountering continuous start-stop operations. Suitable for older models and suitable for all seasons.

PERFORMANCE BENEFITS

Servo Taxi Oil

- ☛ Enable easy low temperature starting
- ☛ Minimise fuel and oil consumption
- ☛ Give longer battery life
- ☛ Provide maximum protection to engine parts against rust and corrosion
- ☛ Give good high and low temperature performance in the engine
- ☛ Minimise wear of engine parts
- ☛ Ensure system cleanliness by holding contaminants in finely dispersed state

PERFORMANCE STANDARDS

Meets IS:13656-2002
E-DL 1/E-PL 1 of SAE 20W-50
API SC/CC

CHARACTERISTICS

SAE GRADE	20W-50
Kinematic Viscosity cSt @ 100°C	17.5 – 19.5
Viscosity Index, Min.	120
Flash point (COC), °C Min.	200
Pour Point, °C Max.	(-) 21
TBN, mg, KOH/gm	4.5 – 6.0

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20