

DESCRIPTION

Servo XEE SL 5W-30 is a premium long life, high performance engine oil with fuel economy recommended for new generation petrol vehicles. This oil is blended from high viscosity index base stocks and contain special additives to meet the highest performance standard for Gasoline Engine.

APPLICATION

Servo XEE SL 5W-30 is recommended for new generation petrol vehicles requiring highest performance levels. Meets the requirement of advanced emission norms.

PERFORMANCE BENEFITS

- ☛ Superior wear protection.
- ☛ Superior deposit control.
- ☛ Extended component life.
- ☛ Excellent engine cleanliness.
- ☛ Lower oil consumption
- ☛ Better Fuel Economy
- ☛ Catalytic Convertor Compatible.

PERFORMANCE STANDARDS

- ☛ API SL in gasoline service.
- ☛ Comply with ILSAC GF-4 Performance.

CHARACTERISTICS

SAE GRADE	5W-30
Kin. Viscosity @ 100°C, cSt	10 – 12
Viscosity Index, Min	150
Flash Point, COC, °C, Min	200
Pour Point, Deg C	< (-) 30
TBN, mg KOH/gm	7.0 – 8.0

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20