

PRODUCT DATA SHEET

SERVO XEE SL 0W-20



DESCRIPTION

Servo XEE SL 0W-20 is a high performance engine oil for new generation petrol vehicles. This oil is blended from high viscosity index highly refined base stocks and contain selected additives to meet the performance standards.

APPLICATION

Servo XEE SL 0W-20 is recommended by Maruti Suzuki Ltd for new generation passenger cars using petrol.

PERFORMANCE BENEFITS

- ☛ Superior performance in terms of oxidation stability, dispersancy characteristics and energy efficiency.
- ☛ Excellent sludge control and extra wear protection at high temperatures and severe operating conditions.
- ☛ Outstanding overall engine cleanliness and also provide long engine life.
- ☛ Fuel savings and nil oil top up.
- ☛ Catalytic Convertor Compatible.

PERFORMANCE STANDARDS

- ☛ Meets API SL.

MANUFACTURERS APPROVAL

Approved by Maruti Suzuki for their new generation petrol cars as Fuel efficient engine oil

CHARACTERISTICS

SAE GRADE	0W-20
Kin. Viscosity @ 100°C, cSt	7.8 – 8.4
Viscosity Index, Min	150
Flash Point, COC, °C, Min	200
Pour Point, °C, Max	(-) 42
TBN, mg KOH/gm	6.35 - 7.75

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20