

PRODUCT DATA SHEET

SERVO SUPER MG 20W-40



DESCRIPTION

Servo Super MG 20W-40 is blended from highly refined base stocks and balanced additive package containing shear stable VI improver, metallic detergent, dispersant and anti-oxidant. This oil is formulated to meet lubrication requirements of both gasoline and diesel engines. Servo Super MG 20W-40 is red in colour and suitable for all seasons.

APPLICATION

Servo Super MG 20W-40 is recommended for

- ☞ Modern passenger cars
- ☞ Naturally aspirated diesel engines operating under severe conditions.
- ☞ Supercharged diesel engines
- ☞ Vehicles encountering continuous start-stop operation.

PERFORMANCE BENEFITS

- ☞ Enable easy low temperature starting
- ☞ Give longer battery life
- ☞ Provide maximum protection to engine parts against rust and corrosion
- ☞ Give good high and low temperature performance in the engine
- ☞ Minimise wear of engine parts
- ☞ Ensure system cleanliness by holding contaminants in finely dispersed state
- ☞ Extended drain interval

PERFORMANCE STANDARDS

* API CF4 / SG

CHARACTERISTICS

SAE GRADE	20W-40
Kinematic Viscosity, cSt @ 100°C	13.5 – 15.5
Viscosity Index, Min.	110
TBN, mg KOH/g	9.5 – 12.5
Flash Point, (COC)°C, Min.	200
Pour Point °C, Max.	(-) 21
Sulphated Ash % wt	1.24 – 1.48

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20