

PRODUCT DATA SHEET

SERVO SUPERIOR XEE 5W-30



DESCRIPTION

Servo Superior XEE 5W-30 oil is high performance engine oil for new generation petrol vehicles. These oils are blended from high viscosity index highly refined base stocks and contain selected additives to meet the superior performance standards.

APPLICATION

Servo Superior XEE 5W-30 is recommended for new generation passenger cars using petrol.

PERFORMANCE BENEFITS

- ☛ Superior performance in terms of oxidation stability, dispersancy characteristics and energy efficiency.
- ☛ Excellent sludge control and extra wear protection at high temperatures and severe operating conditions.
- ☛ Outstanding overall engine cleanliness and also provide long engine life.
- ☛ Fuel savings and nil oil top up.
- ☛ Catalytic Converter Compatible.

PERFORMANCE STANDARDS

- ☛ Meets API SG Plus

MANUFACTURERS APPROVAL

Approved by M/s. Maruti Udyog Ltd for their SX 4 passenger cars.

CHARACTERISTICS

SAE GRADE	5W-30
Kin. Viscosity @ 100°C, cSt	10 – 12
Viscosity Index, Min.	145
Flash Point, COC, °C, Min	160
Pour Point, °C, Max	(-) 33
TBN, mg KOH/gm	7.0 – 8.5

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20