

PRODUCT DATA SHEET

SERVO TRANSDEX III



DESCRIPTION

Servo Transdex III is a high performance Automatic Transmission Fluid (ATF). This oil is blended from selected base stocks and additive system to meet the stringent performance requirement. The fluid is compatible with seal materials used in transmission systems.

APPLICATION

Servo Transdex III is recommended for automatic transmission and power steering units of automobiles like car and light trucks fitted with GM or Ford automatic transmissions.

PERFORMANCE BENEFITS

- Has low co-efficient of friction
- Provides better oxidation stability and low temperature flow.
- Minimise formation of sludge and varnish, thus maintains the system clean.
- Has desired fluid characteristics for smooth operations over a wide range of ambient temperatures.
- Protects parts against rusting even during idle period.
- Help in wear prevention.

PERFORMANCE STANDARDS

- (Dexron III) of General Motors, U.S.A.
- (Mercon V) of Ford Motors.
- Allison C4 Transmission Fluid

CHARACTERISTICS

GRADE	Servo Transdex III
Kin. Viscosity @ 100°C, cSt	7.0 – 7.5
Viscosity Index, Min.	170
Pour Point, °C, Max	(-) 42
Flash Point, COC, °C, Min	170

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20