

PRODUCT DATA SHEET

SERVOPRIME T



DESCRIPTION

Servoprime T oils have been specially formulated to satisfy the demanding requirements of modern high-output steam turbines including their gear units. These oils show exceptionally good oxidation stability, excellent demulsibility and prevent foaming tendency. These oils also possess good air release property. These properties are retained during prolonged service life and helps in giving outstanding performance and trouble free service.

PERFORMANCE BENEFITS

- # Outstanding oxidation and thermal stability that ensure long trouble free service life.
- # Provide excellent antiwear protection.
- # Give excellent long term protection against rust and corrosion.
- # Prevent foaming tendency.
- # Release entrained air quickly.
- # Readily separates out water.

APPLICATION

Servoprime T oils are recommended for use in the lubrication system of steam, gas and water turbines operating under all service conditions. In addition, Servoprime T oils provide outstanding performance in hydraulic systems, circulation systems, enclosed bearings and other industrial machines in which long trouble free service of lubricant is required.

PERFORMANCE STANDARDS

Servoprime T oils exceed the following specifications :

- # Brown Boveri HTGD 90117
- # GEK 28143
- # SIEMENS (TLV 901304)

GEC Alsthom, France against GEK 28143A specification for Gas Turbine.

CHARACTERISTICS

ISO VG GRADE	32T	46T	57T	68T
Kinematic Viscosity, cSt @ 40°C	29-33	43-48	55-60	64-72
Viscosity Index, Min.	100	98	95	95
Flash Point, (COC), °C Min.	200	200	210	210
Pour Point, °C Max.	(-) 6	(-) 6	(-) 6	(-) 6
Neutralisation No. mg KOH/gm	0.2	0.2	0.2	0.2
Rust Test, (D-665 B, 24 hrs.)	Pass	Pass	Pass	Pass
FZG Rating Failure Stage	8 th	8 th	8 th	8 th
Air Release value @ 50 Deg C, Min. Max	4.0	4.0	5.0	5.0

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20