

DESCRIPTION

ServoChainlube FG series of oils are fully synthetic high performance anti-wear chain lubricants specially formulated for the lubrication of drive and transport chains in the food and beverages industries. ServoChainlube FG oils are formulated with select synthetic fluids and additives suitable to meet the stringent requirement of the food processing industries.

APPLICATION

ServoChainlube FG oils are recommended for lubrication of drive and transport chains in food industries. These products are recommended for the application where there is potential for incidental food contact.

PERFORMANCE BENEFITS

- Ensures extension of life of chains and other related components.
- Superior wear and corrosion protection.
- Reduced machine downtime
- No pungent odour and taste
- Low pour point
- Low volatility
- High viscosity index ensures use at wide temperature range.

PERFORMANCE STANDARDS

ServoChainlube FG grades approved by National Sanitary Foundation (NSF), White Book for H1 category lubricants for use in Food Processing Industry.

CHARACTERISTICS :

ISO VG	150	220
Kinematic Viscosity cSt @ 40°C	135 – 165	200 – 240
Kinematic Viscosity cSt @ 100°C	19.13	25.93
Viscosity Index, Min	149	151
Pour Point, °C, Max	(-)33	(-)33
Flash Point, COC, °C, Min	230	230
TAN mg KOH/g, Max	0.80	0.80

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051 May-20

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in