

DESCRIPTION

Servogrease FG EP 2 is formulated with synthetic based stock and aluminium complex thickener fortified with select additive. This grease is developed for lubrication of bearing, motors, shafts which are exposed to shock load and requires extreme pressure protection. Servogrease FG EP 2 is free from odour.

APPLICATION

Servogrease FG EP 2 is recommended for lubrication of bearings and other machineries which are exposed to high load. This product is recommended for the application where there is potential for incidental food contact.

PERFORMANCE BENEFITS

- Protects from rust and corrosion
- Excellent anti-wear property.
- Protection from high and shock load.
- Excellent water resistant property.
- Can be used in centralized greasing system because of smooth structure and very good pumpability.
- Can be used at high temperature

PERFORMANCE STANDARDS

Servogrease FG EP 2 is approved by National Sanitary Foundation (NSF), White Book for H1 category general purpose synthetic grease for Food Processing Industry.

CHARACTERISTICS :

	Servogrease FG EP 2
Colour	Colourless
Worked Penetration @ 25 deg C	265 – 295
Dropping Point, Deg C	250 Min
Waterwashout @ 100 Deg C, 1 hr % wt.	10 max
Oxidation stability test	10.0 max
Base oil Viscosity @ 40 Deg C, cSt	90 – 110
Weld Load , Kg	200 Min

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20