

PRODUCT DATA SHEET

SERVOSYSTEM 22-150



DESCRIPTION

Servosystem oils are anti-wear hydraulic and circulation oils specially formulated for efficient lubrication of a wide variety of industrial equipment. Servosystem oils are blended from highly refined base stocks and carefully selected antioxidant, anti-wear, anti-rust and anti-foam additives.

PERFORMANCE BENEFITS

Servosystem oils

- Provide good wear- protection, thereby prolonging service life of moving parts
- Possess high film strength properties which help minimise friction and wear
- Provide rust-protection, to reduce the incidence of corrosion
- Have excellent resistance to oxidation thereby giving long service life
- Have reduced tendency to foam thereby minimise the chance of noisy operation and erratic actuator response

APPLICATION

Servosystem oils are recommended as fluid media for hydraulic systems and hydraulic pumps even under severe operating conditions in stationary and mobile equipment. These oils are also recommended for circulation, splash, bath and ring oiling systems of the bearings (both plain and anti-friction) and gears of industrial machinery that require a long life lubricant. These oils can be used for chain drives and compressor crankcase lubrication. They are not suitable for lubrication of turbines and silver or silver coated components in any equipment.

PERFORMANCE STANDARDS

- IS: 10522:1983 (Reaffirmed 1993)
- IPSS : 1-09-022

MANUFACTURERS APPROVAL

- Bharat Pumps & Compressors Ltd., Naini
- Hindustan Machine Tools Ltd., Bangalore
- Kirloskar Bros. Ltd., Pune
- Heavy Engg. Corporation, Ranchi
- Revathi CP Equipments

CHARACTERISTICS

GRADE	22	32	46	57	68	81	100	150
Kinematic Viscosity, cSt @ 40°C	20-24	29-33	43-48	55-60	64-72	78 - 85	95-105	145-155
Viscosity Index, Min	95	95	95	95	95	95	90	90
Flash Point (COC), °C Min.	160	190	200	210	210	210	210	230
Pour Point, °C Max.	(-) 6	(-) 6	(-) 6	(-) 6	(-) 6	(-) 6	(-) 6	(-) 6
Rust Test, (D-665 A&B, 24 hrs.)	Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20