

DESCRIPTION

Servo ELGI Recip Airlube is high performance compressor oil, which provides superior antiwear protection, excellent oxidation and thermal stability, resulting longer drain interval. ELGI Recip Airlube provides trouble free service.

PERFORMANCE BENEFITS

Servo ELGI Recip Airlube

- # ensures long service life due to outstanding oxidation and thermal stability.
- # minimize carbon deposit on valve / sleeves / vent.
- # provides protection against rust and corrosion.
- # excellent water separation capacity
- # minimum wear
- # superior performance under severe load.
- # reduced oil consumption.
- # enhanced component life.

APPLICATION

Servo ELGI Recip Airlube is recommended for lubrication of reciprocating compressors requiring oil of excellent thermal stability. This oil is also recommended for sophisticated high performance electro-hydraulic or numerically controlled systems.

MANUFACTURER'S APPROVAL

Servo ELGI Recip Airlube is approved by M/s. ELGI, Coimbatore as Genuine Oil for their reciprocating compressors with a drain interval of 500 hours.

CHARACTERISTICS

ISO VG GRADE	150
Kinematic Viscosity @ 40°C, cSt	146 - 154
Viscosity Index, Min	95
Flash Point (COC), °C, Min	220
Pour Point, °C, Max	(-)3
Emulsion Test D-1401, 40-37-3, Minutes, Max	20
CCR, DIN 51358, Max	3.0

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20