

DESCRIPTION

Servoneum oils are high quality mineral lubricants formulated for the lubrication of pneumatic equipments.

These oils possess excellent load carrying ability and rust preventive characteristics.

APPLICATION

Servoneum oils are recommended for the lubrication of a wide range of pneumatic equipments like rock drills, jack hammers, chippers, wagon drills etc. They are also suitable for use in small in-plant pneumatic tools like grinders, filling tools, drills, tappers, impact wrenches etc.

PERFORMANCE BENEFITS

- Possess better fluidity at low temperatures
- Resist deposit formation thereby keeping equipment parts clean
- Superior anticorrosive & antirust properties
- Long service life due to high oxidation and thermal stability
- Higher film strength & excellent load carrying capabilities

CHARACTERISTICS

ISO VG Grade	68	100	181	220	320
Kinematic Viscosity, cSt @ 40 °C	64-72	95-105	175-185	210-230	315-350
Flash Point (COC), °C Min.	190	190	200	230	230
Viscosity Index, Min	90	90	90	90	90
Pour Point, °C Max.	(-) 9	(-) 9	(-) 9	(-) 6	(-) 3
Weld Load, Kg, IP 239	200	200	200	225	225
Wear Scar Dia, mm	0.35	0.35	0.35	0.35	0.35

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

Mar-21