

DESCRIPTION

Servofilm 40 is highly refined straight mineral oil having excellent water separation characteristics and almost colourless product. This oil is blended from hydrotreated high viscosity index base stocks having inherent oxidation and thermal stability with stainless performance.

APPLICATION

Servofilm 40 is suitable for use as carrier oil in textile and dye industry which requires stain free performance. Because of its selected Kinematic Viscosity the dispersant can be uniformly dispersed in the oil.

PERFORMANCE BENEFITS

Servofilm oils

- Have good resistance to formation of deposits and stain at normal operating temperatures.
- Rapidly separate from water.
- Contains very low sulphur.

PERFORMANCE STANDARDS

Servofilm 40 is approved by M/s. Clariant, Thane as Carrier oil

CHARACTERISTICS

	40
Appearance	Clear
Colour	< 0.5
Kin. Vis. cSt @ 40°C	36 - 44
Viscosity Index, Min	95 Min
Flash Point (COC), °C Min	200
Demulsibility @ 54 Deg C in Minutes	40 – 37 – 3 (10 Max)
Sulphur % Wt.	0.03 % Max

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20