

# PRODUCT DATA SHEET

## SERVOLOOM MCWM



### DESCRIPTION

Servoloom MCWM is straight mineral general-purpose lubricating oil. This oil is aromatic type petroleum base oil. This oil is recommended for non-critical all loss lubrication systems. This oil can also be used as fluid sealing medium for gasholder where gas do not react with mineral oil and as filter media in oil bath type air cleaners.

### APPLICATION

Servoloom MCWM is recommended for hand oiling application involving lubrication of bearings, open gears, lightly loaded slides and guide ways of machine tools. This product is widely used in textile and jute mills for lubrication of looms and other equipments. This oil is recommended for use in all loss non-critical application.

### PERFORMANCE BENEFITS

- It has good lubricity properties to take care of a specific lubrication requirement.

### CHARACTERISTICS

SAE GRADE	Servoloom MCWM
Kinematic Viscosity, cSt @ 100°C	20 - 26
Aniline Point, Deg C	48 - 52
Flash Point, (COC)°C, Min.	220
Pour Point °C, Max.	39

### HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

**E-Mail:** servotechserv@indianoil.in **OR** servots@indianoil.in

May-20