

PRODUCT DATA SHEET

SERVOCUT S



DESCRIPTION

Servocut S is soluble type high quality cutting oil, which yields rich milky emulsion with water. Special emulsifier is incorporated to ensure its complete dispersion in water. The emulsion formed is homogeneous and stable in nature and does not split during usage or routine machine shut down periods, under normal conditions. Servocut S contains rust inhibitors, which impart anti-rust and anti-corrosive properties to the emulsion. Carefully selected biocide is incorporated to prevent bacterial growth in the emulsion.

PERFORMANCE BENEFITS

- Has superior cooling and lubricating properties which contribute towards clean work, excellent surface finish and minimum tool wear.
- When used as a grinding coolant, contribute towards long grinding wheel life, and minimized wheel loading.
- Provides long lasting stable emulsions
- Protects work-piece, machine components and tool materials from rust and corrosion.
- Enables obtain superior finish and accurate tolerances to the parts machined.

APPLICATION

Servocut S is recommended for variety of cutting operations on ferrous and non-ferrous metals. The oil is specially suitable for metal working operations where the cooling property is more desirable compared to the lubricating characteristics.

This grade can also be used with advantage in cold rolling of steel and not rolling of aluminium. To obtain stable emulsion, oil should be added to water and not vice versa. A homogeneous dispersion of oil in water can be obtained by continuous stirring either manually or mechanically while preparing the emulsion.

Servocut S is normally used for concentration of 5% for most of the machining operations. For grinding operations more dilute emulsions are preferred.

PERFORMANCE STANDARDS

Servocut S meets the following specifications
IS : 1115-1986 (Reaffirmed 1996)

CHARACTERISTICS

Kinematic Viscosity, cSt @ 40°C (typical)	20 - 25
Flash Point (COC), °C Min.	150
Copper strip corrosion @ 100°C	1
Cast Iron Corrosion test, 0/1-1	Pass

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

May-20