



SERVO GEM RR

GRADES AVAILABLE – SERVO GEM RR3

DESCRIPTION

Servo Gem RR3 is a premium quality lithium soap grease manufactured from high quality base oils. This grease has excellent resistance to water washout, superior oxidation stability and high degree of anti-rust and anti-corrosion properties. This grease is specially developed for lubrication of anti-friction bearings of railway axle boxes, locomotives and electric motors to give longer service life.

APPLICATION

Servo Gem RR3 is recommended for wheel bearing application in automobiles with enhanced equipment and grease life.

It is suitable for lubrication under sub-zero and reasonably high temperature (140 deg C) conditions.

PERFORMANCE BENEFITS

- Provides superior resistance to structural and consistency changes over wide range of temperatures but remains in place despite severe working or sustained shock impact.
- Have excellent low and high temperature properties. It can be dispensed at sub zero and reasonably high temperature(140 deg C) conditions.

PERFORMANCE STANDARDS

- AAR M 942-88 (modified)
- RSDO specification WD-17 Misc 92

Approved by RDSO, Lucknow. Also approved by Ashok Leyland, Bajaj Auto.

CHARACTERISTICS

Colour	Brown
Structure	Smooth
Soap Type	Lithium
Worked Penetration, @25 °C, (60 Strokes)	220-250
Drop Point °C, Min	180

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai – 400 051.

E-Mail: tservices@indianoil.co.in OR tech_services@indianoil.co.in

